


TS2V



- 1 - Conductor: flexible Nickel
- 2 - P.T.F.E. Tape
- 3 - Electroglass spiral impregnated with silicone rubber
- 4 - Electroglass spiral impregnated with silicone rubber
- 5 - Electroglass braid impregnated with silicone rubber

CHARACTERISTICS:

Operating temperature of insulation materials: -40°C to +320°C
 Operating voltage: 300/500 V
 Test voltage: 1000 Vac for 1 minute

DESCRIPTION	CONDUCTOR CONSTRUCTION Nichel n° strands x wire ø mm	EXTERNAL DIAMETER	
		MIN. mm	MAX. mm
1x1 mm ²	32x0,20	2,30	2,70
1x1,5 mm ²	21x0,30	2,60	3,00
1x1,5 mm ²	21x0,30	2,60	3,00
1x1,5 mm ²	21x0,30	2,70	3,10
1x1,5 mm ²	21x0,30	2,80	3,20
1x1,5 mm ²	21x0,30	2,90	3,30
1x1,5 mm ²	21x0,30	2,60	3,00
1x1,5 mm ²	21x0,30	2,60	3,00
1x1,75 mm ²	25x0,30	2,80	3,20
1x2 mm ²	28x0,30	2,80	3,20
1x2,5 mm ²	20x0,40	3,00	3,40
1x2,5 mm ²	20x0,40	3,00	3,40
1x2,5 mm ²	20x0,40	3,30	3,70
1x2,5 mm ²	80x0,20	3,10	3,50
1x2,5 mm ²	37x0,30	3,10	3,50
1x2,5 mm ²	20x0,40	3,00	3,40